1	4. The method as set forth in claim 1, wherein the mixture of		
2	plastics is subjected to an analysis for material degradation, and the plastics		
3	contained in the mixture of plastics are sorted and separated according to colours if		
4	the analysis establishes that a predetermined degree of degradation has not been		
5	exceeded.		
1	5. The method as set forth in claim 1, wherein plastics (LDPE,		
2	PP) with different melting temperatures, which are obtained as a mixture by means		
	•		
3	of or after separation according to colours, are separated thermally by means of a thermal scanner		
4	thermal scanner		
1	6. The method as set forth in claim 5, wherein the thermal		
2	scanner includes a conveying means comprising a perforated support on which the		
3	plastics (LDPE, PP) to be thermally separated are transported and heated to a		
4	temperature at which at least one of the plastics (LDPE, PP) is in a free-flowing		
5	and at least one other of the plastics (LDPE, PP) is in a solid state of aggregation.		
1	7. The method as set forth in claim 6, wherein a plastic (LDPE)		
2	which has been transferred to a free-flowing state of aggregation by being heated is		
3	collected in a cooling bath to be re-solidified.		
1	8. The method as set forth in claim 1, wherein		
2	the mixture of plastics, having been separated from the non-plastics		
3	contained in a mixture of material, is washed with a washing fluid, and the washing		
4	fluid - together with washed out organic material contained in it - is fed to a bio gas		
5	power station comprising a bio gas generator which generates methane gas from the		
6	organic material by means of micro-organisms;		
7	the methane gas is combusted in a gas turbine; and		
8	a combustion gas from the gas turbine is used to produce processing		
9	energy for sorting and separating the plastics.		
1	9. A plant for recycling plastics and preferably also for		
2	recycling other materials contained in a mixture of refuse material, said plant		
3	including:		

SSM-492US

2

4 5	·	t type-separating means with which plastics and plastics are separated;	
3	non-p	mastics are separated,	
6	b) a seco	ond type-separating means with which the plastics	
7	separ	ated from the non-plastics are separated according to	
8	types	of plastic;	
9	wherein		
10	c) the pl	lastics from the first type-separating means are	
11	trans	ported to a colour separating means in which the plastics	
12	are so	orted and separated according to colours and transported	
13	in fra	ctions of colours to the second type-separating means.	
1	10. The p	plant as set forth in claim 9, wherein the colour	
2	separating means comprises a carrousel extractor in which the fractions of plastics,		
3	sorted according to colours, are individually subjected to extraction using a hot		
4	extraction medium.		
_1	11. The r	plant as set forth claim 9, wherein the second	
2	type-separating means comprises a thermal scanner which comprises a conveying		
3	means with a perforated support for plastics and preferably a cooling means		
4	arranged underneath the perforated support, in a hot gas tunnel.		
1	12. The r	plant as set forth in claim 9 further comprising a bio gas	
1 2	-	s generator topped by at least one gas turbine, wherein:	
2	power station with a bio ga	s generator topped by at least one gas turbine, wherein.	
3	the bio gas generator generates methane gas, by means of		
4	micro-organisms, from the organic material removed from the mixture of material		
5	in the plant;		
6	the methane	gas is combusted in the gas turbine; and	
7	a combustion	gas from the gas turbine is used to produce processing	
8	energy and/or the gas turbine is used to produce electrical energy for the plant.		
1	13. The p	plant as set forth in claim 9 further comprising a chip	

and fibre recycling means with which re-processible chips and fibres are obtained in

a multi-stage chemico-thermo-mechanical method from wood refuse separated out 3 from the mixture of material in the plant. 14. The plant as set forth in claim 9, wherein 1 the plastics are subjected to an analysis for material degradation by 2 means of an analysing means; and 3 plastics are only sorted and separated according to colours if a 4 material degradation of the plastics does not exceed a predetermined degree of 5 6 degradation, and where they do exceed it, are preferably comminuted into plastic 7 particles to be used as fuel.

Respectfully submitted,

Christopher R. Lewis, Reg. No. 36,201 Attorney for Applicants

CRL/lrb

Enclosure: Version with Markings to Show Changes Made

Dated: November 6, 2001

Suite 301 One Westlakes, Berwyn P.O. Box 980 Valley Forge, PA 19482-0980 (610) 407-0700

The Assistant Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. 18-0350 of any fees associated with this communication.

EXPRESS MAIL

Mailing Label No.: EL743541268US Date of Deposit: November 6, 2001

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10, and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Assistant Commissioner for Patents, Washington, DC 20231

Kathleen Libby